



"If you can imagine it, Nadco will make it stick."

188
(Vinyl Anti-Slip Tape)

Description: Vinyl Anti-Slip Tape is characterized by moderate tensile strength, high elongation and good tear strength. Calendering has built in stresses that are a common cause vinyl shrinkage and affect dimensional stability.

Applications: Recommended surface application temperature is 50°F and above. Vinyl Anti-Slip Tape may be applied to clean, dry and lubrication-free surfaces.

Nominal Values

Shelf Life:	1 year from date of purchase (when stored at 72°F, 50% relative humidity)						
Thickness:	Total product .017 +/- 3%						
Adhesive:	Acrylic pressure sensitive adhesive No. 190 coated (1) one side, dry coating weight 1.5 mils +/- 10%						
Release Liner:	Poly coated (2) two sides, heavy weight 90 lb, white paper, typical maximum 50 grams/inch release (1) one side.						
Peel Adhesion:	PSTC-1 modified, 180 peel values ounces per/lineal inch, typical 72°F on stainless steel.						
	<table border="0" style="margin-left: 100px;"> <tr> <td>Immediate</td> <td>43 oz./1 in.</td> </tr> <tr> <td>24 hour</td> <td>53 oz./1 in.</td> </tr> <tr> <td>7days</td> <td>78 oz./1 in.</td> </tr> </table>	Immediate	43 oz./1 in.	24 hour	53 oz./1 in.	7days	78 oz./1 in.
Immediate	43 oz./1 in.						
24 hour	53 oz./1 in.						
7days	78 oz./1 in.						