



"If you can imagine it, Nadco will make it stick."

189
(Grit Safety Tape)

Description: Grit Safety Tape is a mineral-coated plastic film, one side pressure sensitive adhesive, protected by removable liner.

Applications: Recommended surface application temperature is 50°F and above. Grit Safety Tape may be applied to clean, dry and lubrication-free surfaces.

Nominal Values

Shelf Life:	1 year from date of purchase (when stored at 72° F, 50% relative humidity)				
Thickness:	Total product .0275 +/- 4%				
Adhesive:	Rubber based pressure sensitive adhesive No. 408 coated (1) one side, dry coating weight 2.0 mils +/- 10%				
Release Liner:	Kraft coated (1) one side, 78 lb. brown paper, typical maximum 60 grams/inch release (1) one side.				
Peel Adhesion:	PSTC-1 modified, 180° peel values ounces per/lineal inch, typical 72° F on stainless steel.				
	<table border="0" style="margin-left: 100px;"> <tr> <td>Immediate</td> <td>80 oz./1in.</td> </tr> <tr> <td>24 hour</td> <td>130 oz./1in.</td> </tr> </table>	Immediate	80 oz./1in.	24 hour	130 oz./1in.
Immediate	80 oz./1in.				
24 hour	130 oz./1in.				

All information and testing are based on our best experience and knowledge and does not constitute a warranty of products sold. All Nadco materials are sold with the understanding that the users will independently determine suitability of the end use of our products. We recommend customers test bondability immediately upon lamination or after aging, either accelerated or after a period of time.