



*"If you can imagine it, Nadco will make it stick."*

**P743**

**Photographic Masking Tape**

**TYPICAL APPLICATIONS**

- A versatile, reliable tape for use in photo studios, film processing laboratories, as well as in home dark rooms.
- Recommended for use as a chart tape.
- Opaque, matte surface – the “photographer’s masking tape”
- Engineered expressly for quality photographic reproduction work cropping and edging negative for contact printing.
- Sealing camera bellow and film holders against light leaks.

**ADVANTAGES AND BENEFITS**

- An opaque black, matte finish surface insures the light-free masking required for high quality photo reproduction.
- High quick stick and adhesion.
- Easy, consistent unwind.
- High conformability.
- Hand tearable – no need for cutting tools.

**CONSTRUCTION**

Overall Grade/Function: Photographic masking tape.

Backing: Impregnated paper.

Adhesive: Synthetic Rubber.

**COLOR(S)**

Black Matte (BLK)

**STANDARD WIDTH(S)**

24 mm                      48 mm

**STANDARD LENGTH(S)**

55 m

Contract your Nadco Sales Representative for other available sizes.

	STANDARD	METRIC
Tensile Strength	21lbs/in	Width 36.8 N/10mm
Adhesion to Stainless Steel	50 oz/in	Width 5.47 N/10mm
Thickness	6.1 mils	0.15mm
Elongation	7%	7%
Service Temperature Range	45 F to 100 F	7 C to 38 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Nadco. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fir for a particular purpose and is suitable for the user’s method of application before use.