



"If you can imagine it, Nadco will make it stick."

PG-21

Product: PG-21 High Temperature Masking Tape

Description: A high temperature pressure-sensitive masking tape designed for clean removal from a variety of surfaces after exposure to oven temperatures up to 325°F (163°C) for 30 minutes. (Times and temperature are determined by surface.) Not recommended for outdoor use. PG-21 performs well in wet strip applications. Its easy handling, smooth crepe backing exhibits high strength, excellent conformability to irregular surfaces, and exceptional cornering. Provides resistance to paint flaking and a clean, well defined paint line.

Nominal Values:	Backing	Fine Structured Crepe Paper
	Adhesive	Rubber/Resin
	Adhesion to steel (oz/in of width)	28 (7.7 N/25mm)
	Quick Stick (oz/in of width)	
	To Karft	7 (1.9 N/25mm)
	To Steel	16 (4.4 N/25mm)
	Tensile Strength (lbs/in of width)	26 (113.8 N/25mm)
	Elongation (% at break)	10
	Thickness (mils)	7.3 (0.185mm)

Product Application: Automotive, truck, bus and marine paint masking. Recommended hot to warm removal, but can be removed cold.

Features:

Smooth Crepe, Saturated Backing

Advantages:

Smooth to touch and easy to work with. Straight, clean paint-break line. Highly conformable and flexible. Tear resistant. Solvent resistant.

Special Non-printable Release Coat Controlled Unwind. Resists paint flaking upon removal.

Rubber/Resin Adhesive Good Adhesion and holding power. High temperature resistant. Clean removal. Stain and transfer resistant.

Quarter Packed/Poly Wrapped Easily dispensed from carton. No loose rolls. Easy distribution from storeroom. Less damage handling. Cleaner looking product to operator.

NOTICE: While we believe them to be reliable, the statements and information herein are only for general guidance and are not

warrants or guarantees for accuracy and completeness. The user must by test or otherwise determined suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, our standard terms and