



*"If you can imagine it, Nadco will make it stick."*

## 9511 Blue (High Performance Splicing Tape)

**Description:** A thin, strong, conformable, non-woven tissue coated on both sides with an extremely aggressive high performance acrylic pressure sensitive adhesive system. Other outstanding features are high tack, high adhesion, high shear strength and excellent low and elevated temperature performance.

**Applications:** Repulpable splicing applications. A high performance splicing tape used in the manufacture of paper, plastics, and other continuous web processes. Especially suitable in the manufacture of news print. Thickness conformability is excellent for most irregular and mismatched surfaces.

### TECHNICAL DATA

Thickness		
Adhesive:	3.0 mils (0.0030")	0.0762mm
Substrate:	1.3 mils (0.0013")	0.03302mm
Peel Adhesion (PSTC-1):	50 oz/inch	14.3 N/2.5cm
Shear Adhesion (PSTC-7):	Indefinite @ 2.2 psi	Indefinite @ 15.2 kPa
Tensile (PSTC-31):	6 lbs/inch width	27.2 N/2.5cm
Elongation:	5%	5%
Minimum Application Temperature:	-10°F	-23°C
Maximum Continuous Use Temperature:	300°F	149°C
Release Liner:	55 lb/ream	90 GSM
	Honey glassine	