

Selection Guide

ShockWatch Label Selection Guide

Weight lbs. \ Shipment Size	0-1 CUBIC FEET	1-5 CUBIC FEET	6-15 CUBIC FEET	16-50 CUBIC FEET	50+ CUBIC FEET
0-10	GREEN	GREEN	ORANGE	ORANGE	RED
11-25	GREEN	ORANGE	ORANGE	RED	RED
26-50	ORANGE	ORANGE	RED	RED	PURPLE
51-100	ORANGE	RED	RED	PURPLE	PURPLE
101-250	RED	RED	PURPLE	PURPLE	YELLOW
251-1,000	RED	RED	PURPLE	YELLOW	YELLOW
1,000+	---	PURPLE	YELLOW	YELLOW	YELLOW

Cubic feet = height x width x depth

Product Color Key	
Color:	Product:
Green	L-30
Orange	L-35
Red	L-47
Purple	L-55
Yellow	L-65

Drop Height at Which to Expect Label Activation

COLOR PART #	YELLOW L-65	PURPLE L-55	RED L-47	ORANGE L-35	GREEN L-30
< 100 LBS.	---	12-18" (0.30-0.48 m)	12-24" (0.30-0.60 m)	24-36" (0.60-0.91 m)	36"-OVER (0.91 m-OVER)
> 100 LBS.	6-12" (0.15-0.30 m)	8-16" (0.20-0.40 m)	12-18" (0.30-0.48 m)	---	---

NOTE: Packaging and construction may affect the correlation between drop height and ShockWatch activation. This table is intended as an approximate guide only. Minimal testing is suggested.

Clip & Tube Only and Multi-G Selection Guide

All product is rated at 50 milliseconds

Product Name	Sensitivity	Activation Height (on hard surfaces)
CX85 and CXX85 Clip & Tube Only	10G	Activates at 2"/50.8mm to 4"/101.6mm
CX75 and CXX75 Clip & Tube Only	15G	Activates at 3"/76.2mm to 6"/153.4mm
65MC, CX65 and 65MCD, CXX65 Clip & Tube Only	25G	Activates at 4"/101.6mm to 8"/203.2mm (most commonly used clip)
55MC, CX55 and 55MCD, CXX55 Clip & Tube Only	37.5G	Activates at 6"/153.4mm to 14"/355.6mm
47MC, CX47 and 47MCD, CXX47 Clip & Tube Only	50G	Activates at 8"/203.2mm to 18"/457.2mm
35MC, CX35 and 35MCD, CXX35 Clip & Tube Only	75G	Activation trends at 19"/482.6mm to 24"/609.6mm
30MC, CX30 and 30MCD, CXX30 Clip & Tube Only	100G	Activation trends at 24"/609.6mm to 30"/762mm
Multi-G Clip	25G, 50G, 75G (standard)	Activates at three different levels

MC, CX = clip with one window

MCD, CXX = clip with two windows