



*"If you can imagine it, Nadco will make it stick."*

# 1170M

## DOUBLE COATED SUPER HIGH BOND NON-WOVEN TAPE

**DESCRIPTION**

High tack, double coated non-woven tape with a skin contact grade acrylic adhesive.

**APPLICATIONS**

Premium grade toupee tape

**TECHNICAL DATA**

	IMPERIAL	METRIC
Thickness:		
Adhesive:	7.0 mils (0.0070")	0.1778 mm
Substrate:	2.6 mils (0.0026")	0.0660 mm
Total:	9.6 mils (0.0096")	0.2438 mm
Peel Adhesion:	140 oz/in*	39.6 N/2.5 cm
(Ultimate) PSTC-3	*Cohesive Failure	
Shear Adhesion:		
PSTC-7A 35 hrs @	2.2 psi	15.2 kPa
Tensile:	3.3 lbs/inch width	14.9 N/2.5 cm
Elongation:	33%	33%
Low Temperature		
Application:	-40°F	-40°C
High Temperature		
Resistance:	250°F	121°C
Low Environmental		
Resistance:	40°F	-40°C

**IMPORTANT INFORMATION:**

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities.