



"If you can imagine it, Nadco will make it Stick."®

235

JETGLOSS ON-DEMAND RP51 2.8 mil WHITE KRAFT

TECHNICAL PRODUCT INFORMATION

Caliper: 7.5 mil
 Substance weight: 123.5 lbs./ream (25"x38")

Face Paper

Jetgloss On-Demand, High gloss coated paper designed to be compatible with dye and pigmented ink jet inks.

Substance weight:	59 lbs./ream (25"x38")	ISO536
Caliper:	3.9 mil	ISO534
Opacity:	88%	ISO2471
Gloss:	45%	ISO8254-1

Adhesive:

RP51, Modified acrylic dispersion. Permanent adhesive with good adhesion to all normal substrates, including non-polar surfaces, films and corrugated board. Good low temperature performance.

Tack min:	14 N	FTM 9
Shear min:	3.0 h	FTM 8
PE-looptack min:	10 N	modified FTM 9
Labeling temperature min:	32 °F	
Service temperature range:	-4 °F ... 176 °F	

Not recommended for labeling highly curved surfaces. Shelf life: From the date of manufacture 4 years at 68 °F and RH 50%.

Liner:

2.8 mil White Kraft, White kraft liner. For VIP labelstock where good layflat properties are required.

Substance weight:	47 lbs./ream (24" x 36")	ISO536
Caliper:	2.8 mil	ISO534
Tensile strength MD:	42 lbf/in.	ISO1924
Tensile strength CD:	16 lbf/in.	ISO1924

The above are typical technical values and are given in good faith based upon our most up to date knowledge and experience. As the products are used outside our control we cannot take responsibility for any damage which may be caused using the product.