



"If you can imagine it, Nadco will make it Stick."®

3882

2 MIL FLAME RETARDANT ADHESIVE TRANSFER FILM

DESCRIPTION: A 2 mil (50 micron) premium performance unsupported acrylic pressure sensitive transfer adhesive film, with built-in flame retardant properties. This high performance acrylic system exhibits excellent adhesion to a wide variety of materials. Has excellent oxidation and U.V. resistance for both interior and exterior application.

APPLICATIONS: Primarily used for mounting interior aircraft wall covering panels made of Tedlar, Vinyl, Polyester, Fiberglass reinforced plastics, etc. where excellent flame retardant properties and high holds and heat resistance are required. Also used for high performance laminating and mounting of nameplates, decals and other decorative trim and high performance foams.

Conforms to FOKKER FON1-5954-12

TECHNICAL DATA

	<u>IMPERIAL</u>	<u>METRIC</u>
Thickness:	2 mil (.002 in)	.051mm
Adhesion:		
Peel(PSTC-1)20min dwell:	55.0 oz/inch width	15.4 N/2.5cm
Ultimate Peel	80.0 oz/inch width	22.6 N/2.5cm
Shear (PSTC-7)100 hrs @	2.2 psi	15.2kPa
Adhesive Color:	Translucent White	
Temperature Resistance:	-50°F to 400°F	-46°C to 205°C
Minimum Application Temperature:	40°F	4°C
Release Liner:	55 lb	90 GSM
	glassine moisture stable	

IMPORTANT INFORMATION:

The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using the product, user shall determine the suitability of the product for his/her intended use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods. 4/16/00