



*"If you can imagine it, Nadco will make it Stick."*

**FBD2 | 1/32" BLACK POLYETHYLENE DOUBLE COATED FOAM TAPE | FOAM TAPE**

1/32 in. black closed cell, cross linked polyethylene foam coated on both sides with a general purpose rubber based adhesive. White kraft liner.

**FEATURES & BENEFITS**

- Immediate bond
- Adheres well to irregular surfaces
- Conformable
- Service Temperature ~ 0°F to 150°F

**CONSTRUCTION DIAGRAM**



**TYPICAL APPLICATIONS**

- Plastic extrusion
- Signage
- Wire raceways
- Wire mounts
- Trim
- SDL muntin bars

**CONSTRUCTION**

Rubber Adhesive
1/32" Cross-Linked Closed Cell PE Foam
Rubber Adhesive
White Kraft Liner

**PERFORMANCE**

Tensile Strength (psi) S252	60
Dynamic Shear (psi) S253	65
180° Peel (oz/in) PSTC-101	110
Static Shear S217 (PSTC-107*) *Modified	Minimum Requirement 2.2 psi for 100+ hours
Probe Tack ASTM D-2979-01	975**

\*\* Tack numbers may not be exact value of tack as foam can tear during tack test. Please contact our sales staff for any assistance.