



"If you can imagine it, Nadco will make it Stick."®

Transtherm

Facestock: **Veero™ 44# CTT**

A premium C1S, thermal transfer stock designed with excellent imaging properties for all thermal transfer printers. The properties of the sheet allow for high quality barcode and flexo printing, as well as good smudge resistance. This component is not available for custom constructions.

	Typical Value
Basis Weight:	44 #/3300 ft ²
Caliper:	3.0 mils
Tensile MD/CD:	28 / 17
Tear MD/CD:	39 / 50 grams
Opacity:	87%
Parker Print:	1.5 microns
Brightness:	85%

Adhesive: **VG-219**

A general purpose acrylic adhesive with excellent initial tack and ultimate adhesion to a broad range of substrates. The 30°F minimum application temperature allows use in many applications, from product decoration to barcoded packaging labels. It has excellent wide web and high speed die cutting and stripping characteristics. This component is not available for custom constructions.

	Typical Value
Coat Weight:	11 #/3300 ft ²
Coat Weight:	16.28 grams/m ²
Caliper:	.5 mils
Adhesion to Stainless Steel (90° Peel):	32 oz
Loop Tack	67 oz
Service Temperature:	-65 to 200 °F
Minimum Application Temperature:	30 °F
Shear (1000g):	120 minutes
Shelf Life:	One year, when stored at 72° F and 50% RH

Release Liner: **40# BK**

A bleached kraft liner featuring excellent die cutting and stripping characteristics.

	Typical Value
Basis Weight:	39.6 #/3000 ft ²
Caliper:	2.5 mils
Tensile MD/CD:	35 / 15 #/inch
Tear MD/CD:	42 / 48 grams
Opacity:	64%

Total Product Caliper: 6 mils
Product Basis Weight Per MMSI: 207.49 #

Important Notice

These are typical values and should not be considered a specification. Adhesive properties were tested with a film facestock unless denoted with an asterisk(*)