



"If you can imagine it, Nadco will make it Stick."®

TTrr22
Transfer Premium Plus RR22 40# White Kraft

Caliper: 5.8 mil
 Substance weight: 105 lbs./rem (25" x 38")

Face Paper:

Transfer Premium Plus, A matte-coated, lignin-free label paper. An ultra-smooth, coated face material tailored for thermal transfer printing.

Substance weight	47lbs./ream (25" x 38")	ISO536
Caliper	2.9 mil	ISO534
Tensile Strength MD	28 lbf/in	ISO1924
Tensile Strength CD	17 lbf/in	ISO1924
Roughness	2.0 microns PPS10	ISO8791-4
Opacity	88%	ISO2471
Brightness	85%	ISO2470

Adhesive:

RR22, Rubber-resin dispersion. Removable adhesive for rough substrates, such as corrugated board, and for curved substrates. Can also be used in certain cases as a deep freeze adhesive. Long-term removability from smooth even substrates restricted.

Tack	40 lbs./ream (24" x 36")	ISO536
Caliper	2.4 mil	ISO534
Tensile Strength MD	40 lbf/in	ISO1924
Tear Strength CD	58 gf	ISO1974
Opacity	61%	ISO2471

The above are typical technical values and are given in good faith based upon our most up to date knowledge and experience. As the products are used outside our control we cannot take responsibility for any damage with may be caused using the product.