



"If you can imagine it, Nadco will make it stick."

189Y/B **(Yellow & Black Stripe Antislip Grit)**

Description:

189 Y/B is a mineral-coated film, one side pressure sensitive, protected by a removable liner.

Applications:

Recommended surface application temperature is 50°F and above. 189 Y/B may be applied to clean, dry and lubrication free surfaces. Service temperature of 40° - 200°F.

Shelf Life:

One year from date of purchase when stored at 72°F, 50% relative humidity.

Thickness:

Total product .023" +/- 4%

Elongation:

Zero. There is no elongation.

Adhesive:

Rubber based pressure sensitive adhesive No.408 coated (1) one side, dry coating weight 2.0 mils +/- 10%

Release Liner:

Kraft coated (1) one side, 84# brown paper, typical maximum 60 grams/inch release (1) one side

Peel Adhesion:

PSTC-1 modified, 180° peel values ounces per lineal inch, typical 72°F on stainless steel.

| | |
|-----------|---------------|
| Immediate | 80 oz./l.in. |
| 24 hour | 130 oz./l.in. |

All information and testing are based on our best experience and knowledge and does not constitute a warranty of products sold. All material are sold with the understanding that the users independently determine suitability of the end use of our products. We recommend customers test bond ability immediately upon lamination or after aging, either accelerated or after a period of time.