

"If you can imagine it, Nadco will make it stick."

Hot Melt, Surface Printable Packaging Tape #207

TYPICAL APPLICATIONS

- For manual sealing of medium-weight cartons in normal manufacturing and shipping environments
- May also be used in automated industrial carton sealing applications

PRODUCT FEATURES

- For use on Siat L33, L36, L233 (or equivalent) surface printing presses
- Surface printable with leading brands of solvent inks
- Faster drying times and superior ink anchorage
- Instant, permanent bond to a wide range of substrates and surfaces
- Special release coating for consistent, low-force unwind off the roll
- Performs reliably to the core for efficient tape consumption

CONSTRUCTION

Overall Grade/Function: Production

Backing: 30 micron biaxially oriented polypropylene cast film

Adhesive: Synthetic rubber/resin hot melt

COLOR(S)

WHITE (WHI)	CLEAR (CLR)		TAN (TAN)
-------------	-------------	--	--------------

PHYSICAL PROPERTIES STANDARD

1.9 mils	0.048 mm
27 lbs/in width	47.3 N/10 mm
44 lbs/in width	77.1 N/10 mm
150%	150%
44 oz/in width	4.82 N/10 mm
4 oz/in width	0.44 N/10 mm
15,000+ minutes	15,000+ minutes
35 F to 110 F	2 C to 43 C
-20 F to 150	-29 C to 66 C
	27 Ibs/in width 44 Ibs/in width 150% 44 oz/in width 4 oz/in width 15,000+ minutes 35 F to 110 F

METRIC