



"If you can imagine it, Nadco will make it Stick."®

5903

Outdoor Masking Poly Tape

Product Description

NADCO® Outdoor Masking Poly Tape 5903 is designed for construction, remodeling and maintenance jobs. It is made with heavy duty polyethylene film and synthetic rubber adhesive. It is UV weather resistant and removes cleanly for up to one month with little or no adhesive residue on most opaque surfaces without deteriorating.

Product Construction

Backing	Adhesive	Color	Standard Roll Length	Standard Roll Width
Polyethylene	Synthetic Rubber	Red	60 yds. (54.8 m)	1.88 in. (48 mm)

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	79 oz./in. width (87 N/100 mm)	D-3330
Tensile Strength:	21 lbs./in. width (368 N/100 mm)	D-3759
Elongation at Break:	72%	D-3759
Thickness:	7.5 mils (0.19 mm)	D-3652
Temperature Use Range:	Up to 173°F (78°C)	

Features

- Clean removal from most opaque surfaces up to 30 days.
- UV resistant backing.
- Aggressive rubber adhesive grabs and adheres well to many surfaces.
- Easy to tear by hand.
- Conformable backing.
- Red color for good visibility. Color insures that the tape is not accidentally left on.
- Excellent choice for outdoor holding and window and door masking jobs.

Application Ideas

- Ideal for overspray protection when masking substrates from coatings such as stucco, EIFS, gel coat, and construction coatings.
- Ideal for holding, bundling and securing.
- Can be used on surfaces such as window and door frames to protect them from damage during construction.
- Adhesive layer holds well to irregular surfaces such as sealed masonry or brick.
- Excellent for temporary repairs on the job.

2240 72nd Terrace East / Sarasota, FL 34243

800.839.9018 / PH: 941.751.6693 / FX: 941.727.8221 / nadcoinc.com

Storage

Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% RH in the original carton.

Shelf Life

To obtain best performance, use this product within 18 months from date of manufacture.

Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that NADCO® believes are reliable, but the accuracy or completeness of such information is not guaranteed.

**Warranty,
Limited Remedy,
and Disclaimer**

Many factors beyond NADCO®'s control and uniquely within user's knowledge and control can affect the use and performance of a NADCO® product in a particular application. User is solely responsible for evaluating the NADCO® product and determining whether it is fit for a particular purpose and suitable for user's method of application. Unless an additional warranty is specifically stated on the applicable NADCO® product packaging or product literature, NADCO® warrants that each NADCO® product meets the applicable NADCO® product specification at the time NADCO® ships the product. NADCO® MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the NADCO® product does not conform to this warranty, then the sole and exclusive remedy is, at NADCO®'s option, replacement of the NADCO® product or refund of the purchase price.

Limitation of Liability

Except where prohibited by law, NADCO® will not be liable for any loss or damage arising from the NADCO® product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.