



"If you can imagine it, Nadco will make it stick.®"

79449

Destructible Satin Vinyl/S730/50#SCK

(Standard shelf life is amended to 6 months from date of purchase when stored at 70°F/50% R.H.)

Facestock	Facestock physical properties					
2 Mil destructible Vinyl is a satin white cast vinyl film designed specifically for security labeling. Care should be taken in qualifying a particular die configuration to ensure proper strippability. Standard shelf life is amended to 6 months from date of purchase when stored at 70° F/50% R.H.			Imperial value	Units	Metric value	Units
	Caliper: ASTM D1000		0.0020		50.80	micron
	Tensile: ASTM D882	MD	5	psi	0	
		CD	5	psi	0	

Adhesive	Adhesive physical properties					
S730 is a clear solvent acrylic permanent adhesive for general purpose industrial applications. Features good initial tack and ultimate adhesion to a wide variety of substrates including medium to low surface energy plastics, and high shear for minimal cold flow or ooze characteristics.			Imperial value	Units	Metric value	Units
	Type:		Solvent acrylic			
	Caliper: ASTM D1000		0.0009	inches	22.86	micron
	Standard Coat Wt:				27	g/sq m
	Minimum Appl Temp:		50	°F	10	°C
	Service Temp Range:	Min	-40	°F	-40	°C
		Max	300	°F	149	°C
	Loop Tack Stainless Steel: PSTC11		59.2	Oz/inch	65.1	N/100 mm



"If you can imagine it, Nadco will make it stick."

Liner	Liner physical properties					
50#SCK is a bleached, super calendered kraft paper liner with very good diecutting and matrix stripping properties. Supplied with an anti-block coating on the backside of the liner to control ad hesive and label transfer to the backside of the liner in finished, wound rolls. This liner should not be used in fanfolded label applications, and is not recommended for back printability.			Imperial value	Units	Metric value	Units
	Caliper: ASTM D1000		0.0032	inches	81.2800	micron
	Basis Wt: TAPPT T410 *(24” x 36” 500 sheets)		54.0	Lbs/ream	86.4	g/sq m
	Tensile: ASTM D882	MD	48.0	lbs/inch	211.2	N/25 mm
		CD	26.0	lbs/inch	114.4	N/25 mm
	Tear: TAPPI T414	MD	1.7	ounces	48.3	grams
		CD	2.0	ounces	56.8	grams

Liner Release: TMLI 90° removal of liner from facestock	Total construction caliper (approximate):	
Rate of removal	Grams/2" width	
400 inches/min.	20	0.0063 inches (6.3 mils; 160 microns)

Features and Benefits

Opaque white satin vinyl with excellent hiding power.

Fragile facestock tears very easily for tamper evidence.

Clear acrylic general purpose permanent adhesive with good adhesion to most metals, paints, and plastics.

Inherently flexo printable surface

Anti-block coating on the back of the liner.

Note: Although the adhesive is suitable for use up to 300°F, the facestock is limited to 225°F

Applications and Uses

Security labels and seals

Tamper-proof or tamper evident labels

Warranty labels

Authentication marks

Printing and Converting

Destructible vinyl is printable with most standard flexographic and UV letterpress inks. For specific diecutting requirements consult the Technical Marketing Bulletin for material. Due to manufacturing requirements, there might be a maximum of 15 splices per 1,668 yards. It is strongly recommended that the product be converted and applied to substrate within 6 months of purchase. Due to inherent properties of this unique product, facestock shrinkage does occur. Exposure to environmental conditions other than those recommended will accelerate facestock shrinkage or liner growth. Either condition can make the product unusable. Not recommended for automatic application.

2240 72nd Terrace East / Sarasota, FL 34243

800 839.9018 / PH: 941 751.6693 / FX: 941 727.8221 / nadco-inc.com



"If you can imagine it, Nadco will make it stick.®"

RoHS/Regulation 2002/95/EU

The substances listed in article 4 lid 1 of 2002/95/EU (RoHS) are not intentionally used in this product. The concentration limits of these substances will not exceed the set maximum concentration limits as provided in the proposed amendment for 2002/95/EU.

Optimal storage conditions

Unless otherwise specified in this document, ideally stores at 72F and 50% RH

Note:

The technical data presented is from tests we believe to be reliable but should be considered representative or typical only and should not be used for specifications purposes. This product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.

Appendix

Performance Data:

The following technical data should be considered representative or typical only and should not be used for specification purposes. This data was obtained with the adhesive applied to 2 mil polyester facestock. It is not possible to conduct these tests with this facestock due to the fragile nature of the facestock.

	Initial (15 minute dwell)		72 Hours at Room Temperature		72 Hours at 120°F		96 Hours at 150°F (65°C) & 80% Relative Humidity	
Surface	Oz/in	N/100mm	Oz/in	N/100mm	Oz/in	N/100mm	Oz/in	N/100mm
1.Aluminum	77.1	84.8	70.2	77.2	86.2	94.8	112.6	123.9
2.Stainless Steel	67.7	74.5	84.8	93.3	90	99	124.3	136.7
3. ABS Plastic	58.9	64.8	77.8	85.6	73.3	80.6	54.6	60.1
4.Polypropylene	24	26.4	0	0	11	12.1	1	1.1
5.HDPE	11.7	12.9	4.4	4.8	11	12.1	20.5	22.6
6.LDPE	11	12.1	13.2	14.5	8.8	9.7	1.4	1.5



"If you can imagine it, Nadco will make it stick.®"

Environmental Performance: Chemical resistance test results

The performance results are based on 4 hour immersions at room temperature unless otherwise noted (gasoline is 1 hour). Samples were applied to stainless steel and conditioned for 24 hours before immersion and evaluated immediately upon removal. Adhesion measured at 180° peel.

	Adhesion to Stainless Steel		Visual	Edge
Chemical	Oz/in	N/100mm	Appearance	Penetration mm
1. 70% IPA	81.5	89.7	No change	0
2. Tide Detergent	72.5	79.8	No change	0
3. Engine Oil (10W30)	76.8	84.5	No change	0
4. Water	36.7	40.4	No change	0
5. Ammonia	29.6	32.6	No change	0
6. 409 Cleaner	38.7	42.6	No change	3.1
7. Toluene	33.7	37.1	No change	6.4
8. Brake Fluid	79.4	87.3	No change	0
9. Reference Fuel C	50.72	55.8	No change	3.3
10. Kerosense K1	69	75.9	No change	3.1
11. Heptane	60.7	66.8	No change	0

Compliance Recognition:

409 is a registered trademark of the Clorox Company

Tide is a registered trademark of the Procter & Gamble Company

The information on compliance conditions, substrates, and printing products contained in the tables above represent a summary of recognized or acceptable conditions and printing products. Other conditions, substrates, and printing products may be recognized with this material. Please consult the specific compliance organization records or specific files for a complete listing.