



"If you can imagine it, Nadco will make it stick.®"

8088

Description:

BOPP UV treated 40 micron polypropylene film tape coated with excellent UV resistant solvent acrylic adhesive used to splice treated and non-treated plastic substrates. Bonds extremely well to most surfaces including insulating house wraps and insulation boards.

Main Qualities:

- *Excellent adhesion to insulation boards*
- *Good low temperature performance*
- *Good UV stability*
- *Good high temperature performance*

Applications:

- *Overlaps splicing of insulation boards*
- *To seam overlapping house-wrap films*
- *Splicing of paper, polyethylene, polyester, polypropylene and PVC in the web manufacturing process*
- *Repairing of tears in films*
- *Splicing and repairing greenhouse film*

Technical Data:

- | | |
|----------------------------------|--------------------------------------|
| • <i>Color</i> | <i>Red/White</i> |
| • <i>Backing</i> | <i>UV Treated polypropylene film</i> |
| • <i>Adhesive</i> | <i>Acrylic solvent based</i> |
| • <i>Thickness</i> | <i>3.0 mils</i> |
| • <i>Adhesion</i> | <i>40 oz/in</i> |
| • <i>Tensile Strength</i> | <i>30 lbs/in</i> |
| • <i>Elongation</i> | <i>140%</i> |
| • <i>Application Temperature</i> | <i>14°F-122°F</i> |
| • <i>Temperature Resistance</i> | <i>212°F</i> |
| • <i>Roll Length</i> | <i>50m</i> |

Standard Sizes:

48mm x 50m (36 rolls/case)

72mm x 50m (24 rolls/case)

2240 72nd Terrace East / Sarasota, FL 34243

800 839.9018 / PH: 941 751.6693 / FX: 941 727.8221 / nadco-inc.com