



*"If you can imagine it, Nadco will make it stick."*

# 921L

## POLYETHYLENE TAPE

### DESCRIPTION

A nominal 5 mil (125 micron) thick, strong and conformable polyethylene film tape coated with a very high shear, UV resistant acrylic adhesive with excellent holding properties and cold stick. Excellent resistance to moisture, alkalis, oils, abrasion and weathering.

### APPLICATIONS

Primarily used underground for protecting metal, steel, and PVC pipe.

### TECHNICAL DATA

	IMPERIAL	METRIC
Thickness:	5.9 mils (0.0059")	0.1499 mm
Adhesion:		
Peel (PSTC#1):	62 oz/inch width	17.2 N/2.5 cm
Hold(PSTC#7): 96+hrs@	2.2 psi	15.2 kPa
Tack(PSTC#6): rolling ball	2 inch	50.8 mm
Tensile:	12.5 lbs/inch width	55.6 N/2.5 cm
Elongation:	250%	250%
Minimum Application Temperature:	-10°F	-23°C
High Temperature Resistance:	175°F	80°C

#### IMPORTANT INFORMATION:

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities. 1/28/0