



*"If you can imagine it, Nadco will make it stick.®"*

## **CP 905** **High Performance Grade, High Temperature Masking Tape**

---

### **TYPICAL APPLICATIONS**

For high temperature – up to 350 F – paint masking applications in the transportation (auto, coaches, buses and marine) industry.

### **PRODUCT FEATURES**

- High adhesion
- Easy to unwind
- High initial tack and good adhesion to itself
- Clean, flat edges for sharper paint lines
- Residue – free removal
- High temperature stability through multiple bake cycles
- Temperature resistant up to 350 F
- Heavy duty crepe backing is tear – and silver – resistant

### **CONSTRUCTION**

- Overall Grade/Function: High Performance
- Backing: Fine structured crepe (FCS)
- Adhesive: Rubber-based

### **STANDARD WIDTH(S)**

24 mm   36 mm   48mm   72mm   96mm   144mm

### **STANDARD LENGTH(S)**

55m  
Contact your NADCO® sales representative for other available sizes.

### **APPLICABLE STANDARDS**

ASTM D 6123/D 6123M-97 (2012), Type 1

### **STORAGE AND USAGE CONDITIONS**

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other containments.

### **COLOR(S)**

Natural

### **PHYSICAL PROPERTIES**

Tensile Strength  
Adhesion to Stainless Steel  
Thickness  
Elongation  
Service Temperature Range

### **STANDARD**

24 lbs/in width  
41 oz/in width  
6.4 mils  
11%  
60 F to 350 F

### **METRIC**

42 N/ 10 mm  
4.49 N/ 10 mm  
0.16mm  
11%  
16 C to 176 C