



"If you can imagine it, Nadco will make it Stick."®

DCT100 A

UTILITY GRADE DOUBLE-COATED TISSUE TAPE

DESCRIPTION: Tissue paper, coated both sides with an aggressive pressure sensitive acrylic adhesive that is engineered to bond to almost any surface. Features a 53# glassine kraft paper liner (white).

PRODUCT APPLICATIONS: Core starting, splicing paper and film, mounting and many other general purpose applications that requires the joining of two surfaces. Tissue carrier is hand tear-able. Intended for permanent application. Can resist brief localized environmental temperature conditions up to 386°F (180°C)
Product is not repulpable.

NOMINAL VALUES: The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Adhesive	Solvent Acrylic
Backing	1mil (25E) 10# Tissue
Adhesion to Steel (oz/in of width) PSTC-101	53 (14.5 N/25mm)
Shear Adhesion to Steel (minutes) (1" x 1" x 1000g @ 23°C (73°F))	>10,000
Shear Adhesion to Steel (minutes) (1" x 1" x 500g @ 60°C (140°F))	>6000
Temperature Resistance (Localized)	+356°F (180°C)
Temperature Resistance (Short term)	+250°F (121°C)
Temperature Resistance (Long term)	+140°F (60°C)
Total Thickness w/ liner (mils) PSTC-133	5.5 (0.014 mm)
Liner Type / Thickness (mils) PSTC-133 3.2 (0.08 mm)	SCK - White 3.2 (.08mm)
Color	White

2240 72nd Terrace East / Sarasota, FL 34243

800.839.9018 / PH: 941.751.6693 / FX: 941.727.8221 / nadcoinc.com

TAPES & LABELS NADCO TAPES & LABELS