



PRODUCT DATA SHEET



PGM-UV14

PAINTER'S GRADE MASKING TAPE

UV Resistant (14-Days)

DESCRIPTION:

PGM-UV14 is a 5.2 mil painter's grade blue masking tape with a specially formulated solvent-based natural rubber adhesive system that provides clean removal characteristics and UV resistance – up to 14 days of outdoor exposure. The special characteristic of the adhesive system is that the peel adhesion does not increase with time, allowing for removal off a wide variety of surfaces without surface damage. However, it must be tested for each specific application & conditions.

FEATURES:

Pre-slit rolls (3/4", 1", 1.5", 2" & 3") are individually wrapped with 3" Talon Tape core – perfect for retail sales. Custom sizes and out of stock widths will be custom slit and bulk packed with 3" plain core.



Note: If you require the retail wrapping, please indicate this on your order; should we be out of stock of a pre-slit size, we reserve the right to custom slit and bulk pack for your order, unless otherwise indicated.

PHYSICAL PROPERTIES:

Backing	Saturated Crepe Paper
Adhesive	Solvent-Based Natural Rubber
Total Thickness	5.2 mils
Adhesion to Steel	19 oz/inch
Tensile Strength	27 lbs/inch
Elongation	10%
Application Temperature	80°C/176°F
Max. Temperature Resistance	203°F (95°C) Short Term (30 min)
Color	Blue

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods. (1508VHALPHA01)

TAPES & LABELS
NADCO
TAPES & LABELS