



"If you can imagine it, Nadco will make it stick."

PM200

FACESTOCK (2.0 MIL WHITE MATTE LASER POLYESTER): A 2.0 mil micron bright, white PET with a 52% gloss level. High degree of whiteness and opacity. Top coated for printability using high end digital print methods such as laser and thermal transfer printing. This film has high matching direction stiffness and tensile strength for superior high speed label dispensing. This film is water resistant and very durable.

TYPE: Film FEDERAL REGULATION APPROVAL

CALIPER: 2.0 mil Heavy Metals: YES

Toy Safety: YES

Toy Safety: YES Indirect Food: YES Direct Food: NO

ADHESIVE (#325 GENERAL PERM): A tri-bonded specialty clear acrylic adhesive featuring high initial tack, high shear & high ultimate adhesion with excellent clarity and minimum cold flow. It has outstanding plasticizer, UV, solvent, and occasional water and oil resistance. This is an acid free adhesive.

COAT WEIGHT: Standard ADHESIVE TYPE: Permanent Acrylic SHEAR: 350 minutes MININUM APPLCIATION TEMP: 35° F

SERVICE TEMPERATURE: -25°F to 135°F

FEDERAL REGULATION APPROVAL

Heavy Metals: YES
Toy Safety: YES
Indirect Food: YES
Direct Food: NO

TYPICAL ADHESION VALUES

Stainless Steel

180° Peel: 5.6 (lb/in) Loop Tack: 2.7 (lb/in)

Glass

180° Peel: 2.8 lb/in

Polyethylene

180° Peel: 2.9 lb/in

Corrugated

180° Peel: 4.0 lb/in

Painted Metal

180 ° Peel: 4.6 lb/in

RELEASE LINER (40# sck): A general purpose release liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including diecutting, butt cutting, line scoring and dispensing.

BASIS WEIGHT: 40 lbs/ream

CALIPER: 2.5 mil