



"If you can imagine it, Nadco will make it stick."

## **PM200C**

**FACESTOCK** (2.0 MIL + COATING CLEAR PET): A 2.0 mil clear PET top coated on the face for premium printability. This film is printable via flexo, offset, laser, thermal transfer, and HP Indigo. The super clear gloss coating is scratch resistant and durable. The PET film is water resistant, tear resistant, and will withstand heavy use application.

TYPE: Film
CALIPER: 2.0 mil
BRIGHTNESS: N/A
BASIS WEIGHT: N/A

TENSILE: MD: 10000 TD: 20000 TEAR ELNOGATION: MD: 120% TD: 060%

**ADHESIVE** (#325 GENERAL PERM): A tri-bonded specialty clear acrylic adhesive featuring high initial tack, high shear & high ultimate adhesion with excellent clarity and minimum cold flow. It has outstanding plasticizer, UV, solvent, and occasional water and oil resistance. This is an acid free adhesive.

COAT WEIGHT: Standard ADHESIVE TYPE: Permanent Acrylic SHEAR: 350 minutes MININUM APPLCIATION TEMP: 35° F

SERVICE TEMPERATURE: -25°F to 135°F

## FEDERAL REGULATION APPROVAL

Heavy Metals: YES
Toy Safety: YES
Indirect Food: YES
Direct Food: NO

## TYPICAL ADHESION VALUES

**Stainless Steel** 

180° Peel: 5.6 (lb/in) Loop Tack: 2.7 (lb/in)

Glass

180° Peel: 2.8 lb/in

**Polyethylene** 

180° Peel: 2.9 lb/in

Corrugated

180° Peel: 4.0 lb/in

**Painted Metal** 

180 ° Peel: 4.6 lb/in

**RELEASE LINER (40# sck):** A general purpose release liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including diecutting, butt cutting, line scoring and dispensing.

BASIS WEIGHT: 40 lbs/ream

CALIPER: 2.5 mil