

"If you can imagine it, Nadco will make it stick."

SGOP

(White Semi-Gloss w/ Black Adhesive & 40# Liner)

Face Paper

Raflasilk Opaque, White, lignin-free, on-machine coated, semi-gloss paper with reverse side coating. Multipurpose label paper for high-quality multicolor labels for 'blockout' applications.

Substance weight	57 lbs./ream (25" x 38")	ISO536
Caliper	2.8 mil.	ISO534
Tensile strength MD	33 lbf/in.	ISO1924
Tensile strength CD	15 lbf/in.	ISO1924
Roughness	0.7 microns PPS10	ISO8791-4
Opacity	99%	ISO2471
Brightness	89%	ISO2470
Gloss	78%	Hunter 75°

Adhesive

RP51, Modified acrylic dispersion permanent adhesive. Very good adhesion on a wide variety of substrates.

Tack minimum 14 N FTM 9 Shear minimum 1.0 h FTM 8

PE-looptack minimum 10 N modified FTM 9

Minimum labeling temperature 32°F

Service temperature range - 4°F ... + 176°F

Liner

40# White Kraft (2.5 mil.), White kraft liner. For roll stock applications and photocell dispensing.

Substance weight	42 lbs./ream (24" x 36")	ISO536
Caliper	2.5 mil.	ISO534
Tensile strength MD	45 lbf/in.	ISO1924
Tensile strength CD	18 lbf/in.	ISO1924
Transparency	40%	ISO2469

The above are typical technical values and are given in good faith based upon our most up to date knowledge and experience. As the products are used outside our control we cannot take responsibility for any damage which may be caused using the product.