



"If you can imagine it, Nadco will make it Stick."®

SG

Ultra White Semigloss

Facestock (60# Ultra White Semigloss): A premium coated one side stock with outstanding ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This face offers a 90% brightness and an 88% opacity.

				Federal Regulation Approval	
Type:	Paper	Basis Weight:	60 lb/ream	Heavy Metals:	Yes
Caliper:	3.20mil	Tensile:	MD: 35lb/in CD: 19 lbs/in	Toy Safety:	Yes
Opacity:	88.5%	Tear:	MD: 47 grams CD: 46 grams	Indirect Food:	Yes
Brightness:	90%	Elongation:	MD: n/a CD: n/a	Direct Food:	No

Adhesive (AT150): An all temperature and freezer grade acrylic adhesive with good initial tack and high ultimate adhesion when applied at temperatures as long as -20°F. Very good plasticizer, UV and solvent resistance. AT150 adhesive allows for short term reposition on many substrates, yet displays excellent permanency at room temps.

				Typical Adhesion Values	
Coat Weight:	Standard			Stainless Steel:	
Adhesive Type:	Permanent Acrylic			180° Peel:	5.1 lb/in
Shear:	100 minutes			Loop Tack:	2.90 lb/in ²
Minimum Application Temperature:	-20°F	Federal Regulation Approval		Glass:	
Service Temperature:	-65°F 160°F	Heavy Metals:	Yes	180° Peel:	4.4 lb/in
ACTS Approval:	n/a	Toy Safety:	Yes	Polyethylene:	
		Indirect Food:	Yes	180° Peel:	4.2 lb/in
		Direct Food:	No	Corrugated:	
				180° Peel:	4.7 lb/in
				Painted Metal:	
				180° Peel:	3.1 lb/in

Release Liner (40# SCK L-3): Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Basis Weight: 40 lbs/ream

Tensile: MD: 35lb/in CD: 19 lbs/in

Caliper: 2.5 mil

Tear: MD: 47 grams CD: 46 grams