



"If you can imagine it, Nadco will make it stick."

V079

This is a 3.2 mil white vinyl face stock. The adhesive is a laser safe, outdoor permanent. The liner is a 3.4 mil clay coated lay-flat liner. The face stock is very durable, water resistant, and tear resistant. The liner is printable via flexo, offset, and even some laser. The clay coat allows for optimal feeding inside production digital equipment.

Compliance:

21 CFR175.105 - Indirect Food Contact

PVCW080 3.2 mil White Vinyl

TC50610 #610 (E) – Outdoor, marine grade permanent adhesive. This adhesive is BS5609 compliant and skin safe.

SL03085 3.4 mil Layflat Clay Coated Easy Release

Overall Caliper: 7.2mil

Description

#610 is a high performance pressure sensitive adhesive with aggressive adhesion. It is designed for use with permanent paper, foam, and film labels. This adhesive is suited for outdoor use and compatible with vinyl films.

Features

#610 adhesive is a superior adhesive for use in both indoor and outdoor applications. The adhesive has excellent anchorage to many films. The product works well with tight mandrils as well as exhibiting excellent wet-out characteristics. This adhesive is BS5609 compliant and can be used as a drum label construction. #610 is a skin safe adhesive as well.

Popular Product Uses

- Two liner transfer tape
- Over laminates
- Drum labels
- Outdoor labels
- Test tube labels

Typical Performance Properties

180° Peel to Stainless Steel (lb./in.) (15 min)	3.5
180° Peel to Stainless Steel; (lb./in.) (24 hour)	5.6
PSTC-16, Looptack (lb./in.)	3.8
PSTC-107, Shear Adhesion 1/2" x 1" x 1,000 grams	4.0 hours

Typical Adhesive Properties

Minimum Application Temperature	+35F
Service Temperature Range	-40F - 250F