

"If you can imagine it, Nadco will make it stick." $_{\tiny{\text{\tiny B}}}$

VCC 125

VCC 125 Premium Vinyl-Coated Cloth Gaffers Tape


APPLICATIONS

- •Used to protect and anchor wiring in the photography and film industry.
- Book Binding
- ·Vinyl seat repair
- •Wrapping or bundling wire, metals, and plastics
- Moisture and dust-proof sealing of equipment cases and film canisters.
- •Designed to withstand exterior weather and temperatures applications.

FEATURES & BENEFITS

- Heavy-duty vinyl-coated waterproof cloth with excellent conformability.
- •High tack tape with excellent adhesion for superior performance.
- •Non-reflective, low-gloss backing.
- •Excellent performance over a wide temperature range.
- Clean removal adhesive.
- •High thread count for a clean, straight tear.
- •Tested in accordance with UL723.
- •Complies with VOC requirements of SCAQMD Rule 1168
- •Contributes towards satisfying EQ Credit 4.1 (Low Emitting Materials Adhesive & Sealants) under LEED ®

CONSTRUCTION



PRODUCT DESCRIPTION Single-Coated Construction

Backing:

Vinyl-coated Cloth

Adhesive:

Rubber

Colors:

 Black, Blue, Brown, Gray, Green, Olive Drab, Red, Yellow, White, Neon Green, Neon Orange, Neon Pink, Neon Yellow

TEST DATA

Adhesion to Steel 50 oz/in 5.47 N/cm PSTC-1 Adhesion to Backing 29 oz/in 3.17 N/cm PSTC-1 Tensile Strength 42 oz/in 73.55 N/cm ASTM D Tack (Rolling Ball) 4" Maximum Performance Temp 200 F Flame Spread 15 Smoke Developed 5	Tes	st T	ypical Value	Typical Value (Metric)	Test Method
VOC Content	Adl Adl Ter Tac Ma Fla Sm	hesion to Steel hesion to Backing nsile Strength ck (Rolling Ball) ximum Performance Temp me Spread	50 oz/in 29 oz/in 42 oz/in 4" 200 F 15	5.47 N/cm 3.17 N/cm	ASTM D 1000 PSTC-1 PSTC-1 ASTM D 1000

^{**}Recommended storage conditions: 40-60% Humidity, 60°F-80°F

The information presented herein prepared at Nadco Tapes & Labels, Inc (2240 72nd Terrace East, Sarasota, FL 34243) by qualified technical person to Nadco's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which Nadco Assumes any legal responsibility.